

IP66 Rated 100V Line Extended Temperature Range PA Horn Speakers 30W C 2047



DESCRIPTION

The REDBACK C 2047 is specifically designed for applications where a high level of dust or moisture is present. The speaker is compliant with IP66 dust and hose-proof standard. The horn is manufactured from super-tough UV stabilised ABS, and all exterior metal hardware is stainless steel. Horn speakers have an intrinsically strong midrange presence, and the REDBACK C 2047 has clear speech reproduction to ensure intelligibility of announcements. It can be utilised in installations such as schools, train and bus stations, airports, car parks and cool rooms. Power taps are selectable to suit the power rating of the amplifier or the area to be covered.

FEATURES

- Tough UV stabilised ABS construction
- Operating temperature range -30°C to +55°C
- Stainless steel mounting bracket and hardware
- Compliant with IEC529 / IP66 dust and hose-proof standard
- Selectable 100V line power taps 7.5W, 15W & 30W
- High efficiency driver and line transformer

SPECIFICATIONS

100V LINE POWER TAPS:	7.5, 15 & 30W
SPL:	105dB, 1W @ 1m
	120dB, 30W @ 1m
TEMPERATURE RANGE:	30°C to +55°C
MOISTURE PROTECTION:	IEC529 / IP66
FREQ. RESP.:	500Hz - 7kHz
FLARE DIAMETER:	≈130Ø mm
WEIGHT:	≈1.4ka

^{*} Specifications subject to change without notice.