
MATERIAL SAFETY DATA SHEET

IDENTIFICATION

Product Name: **RF Protek**

Classified as Hazardous according to criteria of Worksafe Australia

Trade Name:

UN No: 1950

Other Name:

Dangerous Goods Class: 2

Flammable Gas

Subsidiary Risk:

Hazchem Code: 2Y

Poisons Schedule: 6

Manufacturers Code: Aerosol 60.0068

Use

A multi-purpose maintenance fluid for dewatering, penetrating, lubricating and protecting against rust and corrosion of all electrical, electronic and mechanical assemblies.

Packaged in 176gm (250ml) aerosol containers. Apply from aerosol.

Composition:

Hydrocarbon solvents, mineral oil, proprietary corrosion inhibitors and water repellants.

CO2 propellant (NON CFC) used in aerosol dispenser.

Physical Description/Properties

Appearance: Colourless fluid

Flash Point: 36 Deg C

Auto Ignition Temp: 250 Deg C

Flammable Limits in Air: Vol%: Lower 0.4 Upper 3.6

Vapour Pressure @ 15.8 Deg C: 4.5mm

Boiling Point: 150-198 Deg C

Specific Gravity: 0.85

Extinguishing Media: CO2, Foam Dry Chemical

Special Procedures: None

Unusual Hazards: None

RF Protek

HEALTH HAZARD INFORMATION

Health Effects

Swallowed: May cause irritation to mouth, throat and digestive system.

Eye: Irritant.

Skin: Irritant, also causes defaulting of skin.

Inhaled: Light headiness, drowsiness and headache.

First Aid

Swallowed: Do not induce vomiting. Give glass of water.

Eye: Mild irritant, flush with water.

Skin: Mild irritant, wash with soap and water.

Inhaled: Remove to fresh air. Seek medical attention.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Limits: TLV 150 ppm TWA AGCITI

Ventilation: Provide sufficient (general and /or local) exhaust to maintain a level below TLV'S.

Personal Protection: Not normally necessary

SAFETY HANDLING INFORMATION

Storage and Transport: Store in a cool dry area.
Classified for transport as class 2 flammable gas, Hazchem code 2Y.

Spills and Disposal: Mop up spills with absorbent material, dispose of in landfill in accordance with local Government regulations.

Fire/Explosive Hazard: Aerosol containers store below 50 Deg C.

CONTACT: TECHNICAL MANAGER (02) 9979 8311 – DATE: 1ST JANUARY 2004
